

POLY

LED Bulkhead Lights

PLY01540KC80NAFW65ON

729900002- Ordering Code



General Information

Mounting Type

Surface

Product Type

LED Bulkhead

IP Rating

IP65

Housing Type

Polycarbonate

LED Binning

McAdam<5

Housing Color

White PC Housing

Input Supply

AC 220-240V, 50/60Hz

Control Gear

Tridonic/Vossloh Schwabe

Control Type

On/Off

Output Power

15W

Fitting Lumens

100lm/W \pm 10%

Beam Angle

Wide Beam 110°

Primary Optics

NA

Secondary Optics

Opal Diffuser

Lumen output

1500lms \pm 10%

Vandal proof

Yes

Mounting height

<4mtrs

Chip Family

Osram

CCT

4000K

Lifetime

50000H

CRI

80

Length

Refer Dimensional table

Height

Refer Dimensional table


Description

Circular surface-mounted weather-proof luminaire For wall or ceiling mounting. With opal polycarbonate diffuser, impact resistant. With finely structured attractive glossy decorative surface. Circular diffuser, spherical, especially dimensionally stable. Luminaire diameter \varnothing 220 and 320 mm, luminaire height 90 & 105mm respectively. Permissible ambient temperature (ta): - +55 °C. IP65, impact resistance level IK10, switchable. The luminaire complies with the fundamental requirements of basic lighting standards

Application Areas

Stairways, Balcony, Patio Spaces, Corridors

Dimensional Details




Dimensional table

1500lms D:220mm, H: 90mm

2000lms D:320mm, H: 105mm

Photometric Diagram



Available CCTS

3000K 30K

4000K 40K

6500K 65K

Available Power

15W 015

20W 020

Available CRI

80 CRI C80

Driver Options

Switched N


IP Rating

IP65 650

Product combinations along with their Ordering codes

Alpha Numeric Code	CCT	Control Type	Lumens	IP Rating	Ordering Code
POLY 15W					
PLY01530KC80NAFW65ON	3000K	On/Off	1500lms	IP65	729900001
PLY01540KC80NAFW65ON	4000K	On/Off	1500lms	IP65	729900002
PLY01565KC80NAFW65ON	6500K	On/Off	1500lms	IP65	729900003
POLY 20W					
PLY02030KC80NAFW65ON	3000K	On/Off	2000lms	IP65	729900004
PLY02040KC80NAFW65ON	4000K	On/Off	2000lms	IP65	729950005
PLY02065KC80NAFW65ON	6500K	On/Off	2000lms	IP65	729900006

Specification Code Details



Customise your product according to your requirement from our website www.oxbridgelighting.com

Refer Instruction Manual for detailed Installation Procedure